

D61-18

Print to 4-67

# YASHICA

## J-5

**All the Features plus enhanced capability—Auto-diaphragm, CdS meter, Self-timer**



f/1.4



## New Top Quality Photography is easier than ever before...\*

With the J-5 whether you're a professional or an amateur you'll find this camera can be enjoyed using day-in-day-out, producing finer photographs consistently and challenging you to achieve the higher levels of photographic endeavor of which it is more than capable of delivering. Read the J-5's features at right, and ask your dealer to demonstrate, hold it, feel its precision and innate capability to match your desires and aspirations.

\*...With CdS exposure control added to enhance an acclaimed camera and lens system. High and low light level sensitivity control plus narrow acceptance angle accurately indicates correct exposure for the most delicate shadow area or sparkling highlights. Your pictures take on added quality from the very start with the YASHICA J-5.

This camera is available with f/1.4 or f/1.8 lenses at your preference.

# J-5

### Convenient Screw Mount

Versatile screw lens mount for precise mounting of accessory lenses and other accessories. Telephoto, wide angle lenses and accessories are screwed into place, providing additional safety for camera and accessories.



### Fully Automatic Diaphragm With Preview Control

Full brightness viewing before and after picture is taken is afforded by new fully automatic diaphragm. Control bar allows aperture to be stopped down to preview depth of field. Extended versatility is provided by eight-second self-timer with separate actuating button.




### CdS Shutter-coupled Exposure Meter

New, super-sensitive Cadmium Sulphide (CdS) exposure meter measures reflected light precisely, even dimmest. Meter is cross coupled to wide range ASA scale and single, non-spinning shutter speed dial with 10 speeds from 1/2 to 1/1,000 sec., B and X. High and low meter sensitivity control switch has "off" position to extend life of mercury battery.



### Instant-return Mirror

Press the shutter release and the lens diaphragm stops down, the mirror snaps up while the film is being exposed and returns instantly upon completion of shutter travel—no blackout—completely automatic. Mirror locks into position upon return, providing precise focusing before and after shutter is wound.



### Single, Non-spinning Shutter Speed Dial

Full 10-speed range from 1/2 to 1/1,000 second, B & X are set on one non-spinning dial which locks in place—cannot be accidentally changed or jarred of setting. Dial is color-coded for hand held and tripod-suggested speeds. Electronic flash (X) and bulb (B) setting have contrasting colors.







# J-5

## FEATURES :

- Extra-sharp AUTO YASHINON-DX 50mm f/1.4 (AUTO YASHINON 55mm f/1.8) hard-coated anastigmat lens with convenient "screw-in" type mount
- Fully automatic diaphragm for clearer, brighter viewing. Preview bar affords quick determination of depth of field
- Super-sensitive Cadmium Sulphide (CdS) exposure meter cross coupled to ASA film speed settings and shutter speed dial
- Three position—high, low, off—control switch.
- Full FP/X flash synchro. focal plane shutter with 10 accurate 1 : 2 progression speeds from 1/2 to 1/1,000 plus X and B settings
- Cross-grid, micro-screen spot for dead-accurate, needle sharp focusing. Focuses as close as 0.55 meter (1.75 ft.)
- Fully automatic film winding, shutter cocking mechanism with double exposure prevention
- High speed, fold-out rapid rewind crank
- Non-spinning single pivot shutter speed dial
- Viewfinder clip for accessories

## YASHICA



**YASHICA CO., LTD.**

**TOKYO JAPAN**